

UNIMIX

WATERFREE READY-FOR-USE LUBRICATION SOLUTION FOR VIBRATION CLEANING PROCEDURE

Description

UNIMIX is a waterfree solution for lubrication of complete watches after the cleaning and a singular rinsing process, e.g. by vibration. *UNIMIX* is also suitable as relubricating rinsing solution after the cleaning and drying of metal precision parts.

Application and dosage

Ready-for-use relubrication solution after the final rinsing process. Shake well before use!

After the cleaning of the watch work with *WF PRO* and the subsequent rinsing with *SUPROL PRO*, the complete watch work is relubricated with *UNIMIX* in the third bath. If no relubrication is required, use *SUPROL PRO* for the second rinsing bath also.

Safety recommendations

UNIMIX is classified as hazardous according to the regulation (EC) No 1272/2008 [GHS] (flammable, eye irritation, narcotic effect, aspiration toxicity, hazardous to the aquatic environment). Observe also with respect to this the hints indicated in the Safety Data Sheet and always handle chemicals with care.

Physical-chemical characterisation

Density: 0.69 - 0.83 g/ml, flash point: 23-25°C. The product is not miscible with water and keeps on top of water. Mixture of solvents free of halogens like chlorine or fluorine with small additions of different oils.

Disposal

1. Disposal regulations same as for used oil / diesel / benzine.
2. Dispose via specialised disposal companies:
European waste code: 14 06 03*, „other solvents and solvent mixtures“.
3. Burn in suitable equipments, but according to official regulations.

Transport in appropriate suitable containers.

Do not discharge into the drains/surface waters/groundwater. Do not discharge into the subsoil/soil. Do not discharge product unmonitored into the environment.

Volumes, storage and transport

Available volumes: 1 litre, 2.5 litre, 5 litre and 10 litre.

Keep in tightly closed original container at a dry, cool and ventilated place and protected from heat and direct solar radiation. Do not store together with oxidizing agents. Do not mix with other chemicals. Keep away from ignition sources.

Shelf life: 3 years from date of production (see stamp on label).

Classification for all means of transport: class 3, UN 3295.

